

# Material Safety Data Sheet



DIESEL FUEL



## 1. Product and company identification

- Product name** : DIESEL FUEL
- Synonym** : Seasonal Diesel, #1 Diesel, #2 Heating Oil, #1 Heating Oil, D50, D60, P40, P50, Arctic Diesel, Farm Diesel, Marine Diesel, Low Sulphur Diesel, LSD, Ultra Low Sulphur Diesel, ULSD, Mining Diesel, Naval Distillate, Dyed Diesel, Marked Diesel, Coloured Diesel, Furnace special, Biodiesel blend, B1, B2, B5, Diesel Low Cloud (LC), Marine Gas Oil.
- Code** : W104, W293
- Material uses** : Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type. Mining diesels, marine diesels, MDO and naval distillates may have a higher flash point requirement.
- Manufacturer** : PETRO-CANADA  
P.O. Box 2844  
150 – 6th Avenue South-West  
Calgary, Alberta  
T2P 3E3
- In case of emergency** : Petro-Canada: 403-296-3000  
Canotec Transportation: 613-996-6666  
Poison Control Centre: Consult local telephone directory for emergency number(s).

## 2. Hazards identification

- Physical state** : Bright oily liquid.
- Odor** : Mild petroleum oil like.
- WHMIS (Canada)** :    
Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Emergency overview** : WARNING!  
COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION.  
Combustible liquid. Severely irritating to the skin. Irritating to eyes. Keep away from heat, sparks and flame. Do not get in eyes. Avoid breathing vapor or mist. Avoid contact with skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling.
- Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.
- Potential acute health effects**
- Inhalation** : Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.
- Ingestion** : Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract.
- Skin** : Severely irritating to the skin.
- Eyes** : Irritating to eyes.
- Potential chronic health effects**
- Chronic effects** : No known significant effects or critical hazards.
- Carcinogenicity** : Diesel engine exhaust particulate is probably carcinogenic to humans (IARC Group 2A).
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.

## 2. Hazards identification

- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Medical conditions aggravated by over-exposure** : Avoid prolonged or repeated skin contact to diesel fuels which can lead to dermal irritation and may be associated with an increased risk of skin cancer.

See toxicological information (Section 11)

## 3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Hydrotreated Renewable Diesel/ Fuels, diesel/ Fuel Oil No. 1/ Fuel Oil No. 2	64742-81-0/ 68334-30-5/ 8008-20-6/ 68476-30-2	95 - 100
Alkanes, C10 – 20 Branched and Linear (R100)	928771-01-1	10 - 20
Fatty acids methyl esters	61788-61-2 / 67784-80-9 / 73891-99-3	0 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

- Flammability of the product** : Combustible liquid
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Products of combustion** : Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), sulphur oxides (SO<sub>x</sub>), sulphur compounds (H<sub>2</sub>S), smoke and irritating vapours as products of incomplete combustion.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 5 . Fire-fighting measures

- Special remarks on fire hazards** : Flammable in presence of open flames, sparks and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite.
- Special remarks on explosion hazards** : Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Runoff to sewer may create fire or explosion hazard.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Ensure the storage containers are grounded/bonded.

## 8 . Exposure controls/personal protection

Ingredient	Exposure limits
Fuels, diesel	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 100 mg/m <sup>3</sup> , (Inhalable fraction and vapour) 8 hour(s).
Fuel oil No. 2	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 100 mg/m <sup>3</sup> , (Inhalable fraction and vapour) 8 hour(s).
Hydrotreated Renewable Diesel	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> 8 hour(s).
Fuel oil No. 1	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> 8 hour(s).

### Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

#### Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

#### Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Recommended: nitrile, neoprene, polyvinyl alcohol (PVA), Viton®. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

#### Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

#### Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9 . Physical and chemical properties

<b>Physical state</b>	: Bright oily liquid.
<b>Flash point</b>	: Diesel fuel and other distillate fuels: Closed cup: $\geq 40^{\circ}\text{C}$ ( $\geq 104^{\circ}\text{F}$ ) Marine Diesel/MDO/Naval Distillate: Closed Cup: $\geq 60^{\circ}\text{C}$ ( $\geq 140^{\circ}\text{F}$ ) Mining Diesel: Closed Cup: $\geq 52^{\circ}\text{C}$ ( $\geq 126^{\circ}\text{F}$ )
<b>Auto-ignition temperature</b>	: $225^{\circ}\text{C}$ ( $437^{\circ}\text{F}$ )
<b>Flammable limits</b>	: Lower: 0.7% Upper: 6%
<b>Color</b>	: Clear to yellow (This product may be dyed red for taxation purposes).
<b>Odor</b>	: Mild petroleum oil like.
<b>Odor threshold</b>	: Not available.
<b>pH</b>	: Not available.
<b>Boiling/condensation point</b>	: $150$ to $371^{\circ}\text{C}$ ( $302$ to $699.8^{\circ}\text{F}$ )
<b>Melting/freezing point</b>	: Not available.
<b>Relative density</b>	: $0.80$ to $0.88$ kg/L @ $15^{\circ}\text{C}$ ( $59^{\circ}\text{F}$ )
<b>Vapor pressure</b>	: $1$ kPa ( $7.5$ mm Hg) @ $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ).
<b>Vapor density</b>	: $4.5$ [Air = 1]
<b>Volatility</b>	: Not available.
<b>Evaporation rate</b>	: Not available.
<b>Viscosity</b>	: Diesel fuel: $1.3$ - $4.1$ cSt @ $40^{\circ}\text{C}$ ( $104^{\circ}\text{F}$ ) Marine Diesel Fuel: $1.3$ - $4.4$ cSt @ $40^{\circ}\text{C}$ ( $104^{\circ}\text{F}$ )
<b>Pour point</b>	: Not available.
<b>Solubility</b>	: Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

## 10 . Stability and reactivity

<b>Chemical stability</b>	: The product is stable.
<b>Hazardous polymerization</b>	: Under normal conditions of storage and use, hazardous polymerization will not occur.
<b>Materials to avoid</b>	: Reactive with oxidizing agents and acids.
<b>Hazardous decomposition products</b>	: May release COx, NOx, SOx, H <sub>2</sub> S, smoke and irritating vapours when heated to decomposition.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Fuels, diesel	LD50 Dermal	Mouse	24500 mg/kg	-
	LD50 Oral	Rat	7500 mg/kg	-
Fuel oil No. 2	LD50 Oral	Rat	12000 mg/kg	-
Fuel oil No. 1	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	>5000 mg/m <sup>3</sup>	4 hours
Hydrotreated Renewable Diesel	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	>5200 mg/m <sup>3</sup>	4 hours

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Irritation/Corrosion

**Conclusion/Summary** : Not available.

### Sensitizer

## 11 . Toxicological information

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Diesel engine exhaust particulate is probably carcinogenic to humans (IARC Group 2A).

### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Fuels, diesel	A3	3	-	-	-	-
Fuel oil No. 1	A3	3	-	-	-	-
Fuel oil No. 2	A3	3	-	-	-	-
Hydrotreated Renewable Diesel	A3	3	-	-	-	-

### Mutagenicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.


## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>TDG Classification</b>	UN1202	DIESEL FUEL	3	III		-
<b>DOT Classification</b>	Not available.	Not available.	Not available.	-		-

## 14 . Transport information

PG\* : Packing group

## 15 . Regulatory information

### United States

**HCS Classification** : Combustible liquid  
Irritating material

### Canada

**WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### International regulations

**Canada inventory** : All components are listed or exempted.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Europe inventory** : All components are listed or exempted.


## 16 . Other information

**Label requirements** : COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION.

**Hazardous Material Information System (U.S.A.)** :

Health	2
Flammability	2
Physical hazards	0
Personal protection	H

**National Fire Protection Association (U.S.A.)** :



**References** : Available upon request.  
™ Trademark of Suncor Energy Inc. Used under licence.

**Date of printing** : 4/14/2014.

**Date of issue** : 28 June 2013

**Date of previous issue** : No previous validation.

**Responsible name** : **Product Safety - DSR**

▣ Indicates information that has changed from previously issued version.

**For Copy of (M)SDS** : Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

### Notice to reader

## 16 . Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



# Material Safety Data Sheet



GASOLINE, UNLEADED



## 1. Product and company identification

- Product name** : GASOLINE, UNLEADED
- Synonym** : Regular, Unleaded Gasoline (US Grade), Mid-Grade, Plus, Super, WinterGas, SummerGas, Supreme, SuperClean WinterGas, RegularClean, PlusClean, Premium, marked or dyed gasoline, TQRUL, transitional quality regular unleaded, BOB, Blendstock for Oxygenate Blending, Conventional Gasoline.
- Code** : W102E, SAP: 102 to 117
- Material uses** : Unleaded gasoline is used in spark ignition engines including motor vehicles, inboard and outboard boat engines, small engines such as chain saws and lawn mowers, and recreational vehicles.
- Manufacturer** : PETRO-CANADA  
P.O. Box 2844  
150 – 6th Avenue South-West  
Calgary, Alberta  
T2P 3E3
- In case of emergency** : Petro-Canada: 403-296-3000  
Canotec Transportation: 613-996-6666  
Poison Control Centre: Consult local telephone directory for emergency number(s).

## 2. Hazards identification

- Physical state** : Clear liquid.
- Odour** : Gasoline
- WHMIS (Canada)** :    
Class B-2: Flammable liquid  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Emergency overview** : WARNING!  
FLAMMABLE LIQUID AND VAPOUR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. CONTAINS MATERIAL WHICH MAY CAUSE HERITABLE GENETIC EFFECTS.  
Flammable liquid. Irritating to eyes, respiratory system and skin. Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapour or mist. Avoid contact with eyes, skin and clothing. Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. Contains material which may cause heritable genetic effects. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
- Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.
- Potential acute health effects**
- Inhalation** : Inhalation of this product may cause respiratory tract irritation. Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.
- Ingestion** : Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract. Ingestion of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.

## 2 . Hazards identification

- Skin** : Irritating to skin.
- Eyes** : Irritating to eyes.
- Potential chronic health effects**
- Chronic effects** : This product contains an ingredient or ingredients, which have been shown to cause chronic toxic effects. Repeated or prolonged exposure to the substance can produce blood disorders.
- Carcinogenicity** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : Contains material which may cause heritable genetic effects.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Medical conditions aggravated by over-exposure** : Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated skin exposure can produce local skin destruction or dermatitis.

See toxicological information (Section 11)

## 3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Gasoline	86290-81-5	85-100
Toluene	108-88-3	15-40*
Benzene	71-43-2	0.5-1.5
Ethanol	64-17-5	0.1-0.3

\*Montreal: may vary from 3-40%

\*Edmonton: may vary from 1-5%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4 . First-aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid (NFPA) .
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Products of combustion** : Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), polynuclear aromatic hydrocarbons, phenols, aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Extremely flammable in presence of open flames, sparks, shocks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. Rapid escape of vapour may generate static charge causing ignition. May accumulate in confined spaces.
- Special remarks on explosion hazards** : Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Containers may explode in heat of fire. Vapours may form explosive mixtures with air.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly

## 7 . Handling and storage

closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Storage

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Ensure the storage containers are grounded/bonded.

## 8 . Exposure controls/personal protection

Ingredient	Exposure limits
Gasoline	<b>ACGIH TLV (United States).</b> TWA: 300 ppm 8 hour(s). STEL: 500 ppm 15 minute(s).
Toluene	<b>ACGIH TLV (United States).</b> TWA: 20 ppm 8 hour(s).
Benzene	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 0.5 ppm 8 hour(s). STEL: 2.5 ppm 15 minute(s).
Ethanol	<b>ACGIH TLV (United States).</b> STEL: 1000 ppm 15 minute(s).

### Consult local authorities for acceptable exposure limits.

### Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### Engineering measures

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

#### Respiratory

- : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

## 8 . Exposure controls/personal protection

- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Recommended: polyvinyl alcohol (PVA), Viton®. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9 . Physical and chemical properties

- Physical state** : Clear liquid.
- Flash point** : Closed cup: -50 to -38°C (-58 to -36.4°F) [Tagliabue.]
- Auto-ignition temperature** : 257°C (494.6°F) (NFPA)
- Flammable limits** : Lower: 1.3% (NFPA)  
Upper: 7.6% (NFPA)
- Colour** : Clear to slightly yellow or green, undyed liquid. May be dyed red for taxation purposes.
- Odour** : Gasoline
- Odour threshold** : Not available.
- pH** : Not available.
- Boiling/condensation point** : 25 to 220°C (77 to 428°F) (ASTM D86)
- Melting/freezing point** : Not available.
- Relative density** : 0.685 to 0.8 kg/L @ 15°C (59°F)
- Vapour pressure** : <107 kPa (<802.5 mm Hg) @ 37.8°C (100°F)
- Vapour density** : 3 to 4 [Air = 1] (NFPA)
- Volatility** : Not available.
- Evaporation rate** : Not available.
- Viscosity** : Not available.
- Pour point** : Not available.
- Solubility** : Hydrocarbon components virtually insoluble in water. Soluble in alcohol, ether, chloroform and benzene. Dissolves fats, oils and natural resins.

## 10 . Stability and reactivity

- Chemical stability** : The product is stable.
- Hazardous polymerisation** : Under normal conditions of storage and use, hazardous polymerisation will not occur.
- Materials to avoid** : Reactive with oxidising agents, acids and interhalogens.
- Hazardous decomposition products** : May release CO<sub>x</sub>, NO<sub>x</sub>, phenols, polycyclic aromatic hydrocarbons, aldehydes, ketones, smoke and irritating vapours when heated to decomposition.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Gasoline	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	13600 mg/kg	-
Toluene	LD50 Dermal	Rabbit	12125 mg/kg	-
	LD50 Oral	Rat	636 mg/kg	-
	LC50 Inhalation Vapour	Rat	7585 ppm	4 hours
	LD50 Dermal	Rabbit	>8240 mg/kg	-
Benzene	LD50 Oral	Rat	930 mg/kg	-
	LC50 Inhalation Vapour	Rat	13700 ppm	4 hours
	LD50 Oral	Rat	7060 mg/kg	-
Ethanol	LC50 Inhalation Vapour	Rat	>32380 ppm	4 hours

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Irritation/Corrosion

**Conclusion/Summary** : Not available.

### Sensitiser

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Gasoline	A3	2B	-	-	-	-
Toluene	A4	3	D	-	-	-
Benzene	A1	1	A	+	Proven.	+
Ethanol	A3	-	-	-	-	-

### Mutagenicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : There is a wealth of information about the teratogenic hazards of Toluene in the literature; however, based upon professional judgement regarding the body of evidence, WHMIS classification as a teratogen is not warranted.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.


## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>TDG Classification</b>	UN1203	GASOLINE	3	II		-
<b>DOT Classification</b>	Not available.	Not available.	Not available.	-		-

PG\* : Packing group

## 15 . Regulatory information

### United States

**HCS Classification** : Flammable liquid  
Irritating material  
Carcinogen

### Canada

**WHMIS (Canada)** : Class B-2: Flammable liquid  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### International regulations

**Canada inventory** : All components are listed or exempted.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Europe inventory** : All components are listed or exempted.

## 16 . Other information

**Label requirements** : FLAMMABLE LIQUID AND VAPOUR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. CONTAINS MATERIAL WHICH MAY CAUSE HERITABLE GENETIC EFFECTS.

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		3
Physical hazards		0
Personal protection		H

**National Fire Protection Association (U.S.A.)** :



**References** : Available upon request.  
™ Trademark of Suncor Energy Inc. Used under licence.

**Date of printing** : 10/10/2012.

**Date of issue** : 10 October 2012

**Date of previous issue** : 4/9/2010.

**Responsible name** : Product Safety - DSR

▣ Indicates information that has changed from previously issued version.

**For Copy of (M)SDS** : Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



**Material Safety Data Sheet****1. Product and Company Identification**

Product Name: Isooctane  
Synonym: Isooctane; Iso-octane; 2,2,4-Trimethylpentane;  
Pentane, 2,2,4-Trimethyl; 2,4,4-Trimethylpentane  
Isobutyltrimethylmethane; TMP  
Product use: Gasoline blending component  
Manufacturer: Keyera Alberta Envirofuels Facility  
Address: 9511-17<sup>th</sup> Street,  
Edmonton, Alberta T6P 1Y3  
MSDS Information: 1-780-449-7910  
Emergency Contact: 1-866-377-7110

**2. Hazards Identification****POTENTIAL HEALTH EFFECTS/ROUTES OF EXPOSURE**

<b>Exposure Route</b>	<b>Acute Health Effects</b>	<b>Symptoms of Exposure</b>
<b>Eye:</b>	May cause mild irritation.	Redness and pain
<b>Skin:</b>	May produce mild irritation.	Redness, rash
<b>Inhalation:</b>	May cause slight irritation of the nose, throat and lungs.	
	Effects on the Central Nervous system (CNS) may range from mild to severe effects such as respiratory depression.	May range from rapid breathing, fatigue, headache, light-headedness to more severe symptoms of dizziness and in extreme cases, respiratory arrest, convulsions or loss of consciousness.
<b>Ingestion:</b>	May be aspirated into lungs if swallowed.	Aspiration into lungs may result in pulmonary edema and chemical pneumonitis.
	May have effects on the CNS.	See "inhalation" above for symptoms of CNS effects.
	May cause gastrointestinal irritation.	Symptoms of gastrointestinal irritation include diarrhea, nausea and vomiting.

**3. Composition/Information on Ingredients**

<b>Ingredient Name</b>	<b>wt %</b>	<b>CAS No.</b>
Isooctane	>85%	540-84-1
Isododecane	<10%	13475-82-6
Paraffins & Isoparaffins	<5%	N/A





distance as possible.

- On ground spills use fire fighting foam to contain vapors. Recommended application rate is 0.1 USGPM/sq. ft. (4.1 L/Min/sq.ft.). This is the application rate for hydrocarbons as per NFPA 11
- Consider evacuation of downwind area if material is leaking.
- If tank, rail car or tank truck is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

**Unusual Fire and Explosion Hazards:**

- The highly flammable vapors are heavier than air and may accumulate in low areas and /or spread along ground to distant ignition sources and flash back.
- Closed containers exposed to heat may explode. (OSHA Class 1B Flammable Liquid).
- Thermal decomposition produces acrid fumes.
- Vapor-air mixtures are explosive above the flash point.

## 6. Accidental Release Measures

- Shut off source, if possible.
- Remove all sources of ignition.
- Evacuate area of all unnecessary personnel.
- Isolate hazard area.
- Keep unnecessary and unprotected personnel from entering.
- Ventilate area of leak or spill.
- Vapors are heavier than air
- Small spills will evaporate.
- Emergency personnel must wear appropriate personal protective equipment.
- Use non-sparking tools and equipment.
- Contain and recover liquid when possible.
- Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container.
- Do not use combustible materials, such as sawdust.
- Avoid runoff into storm sewers and ditches that lead to waterways.
- Have foam or dry powder extinguisher on hand.
- If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.
- Refer to Guide 128 of the Emergency Response Guidebook (Transport Canada/US Dept of Transportation).

## 7. Handling and Storage

**HANDLING PRECAUTIONS**

- Use only in a well ventilated area.
- Avoid contact with eyes, skin, and clothing.
- Avoid ingestion and inhalation.
- Keep product away from heat, sparks and open flame.



- Ground and bond containers when transferring material.
- Use spark-proof tools and explosion proof equipment.
- Take precautionary measures against static discharges.
- Keep container tightly closed.

**STORAGE PRECAUTIONS**

- Protect against physical damage to container.
- Store in a cool, dry, well-ventilated location, away from any area where the fire-hazard may be acute.
- Outside or detached storage is preferred.
- Separate from incompatibles. (See section 10)
- Avoid temperature extremes, explosives, nitrogen-fluorine compounds, sulphites, perchlorates, and plastics.
- Containers should be bonded and grounded for transfers to avoid static sparks.
- Drums must be equipped with self-closing valves, pressure vacuum bungs, and flame arresters.
- Storage and use areas should be No Smoking areas.
- Use non-sparking type tools and equipment, including explosion proof ventilation.
- Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.
- Do not attempt to clean empty containers since residue is difficult to remove.
- Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

**8. Exposure Controls / Personal Protection**

**ENGINEERING CONTROLS**

- Provide local exhaust ventilation to meet regulatory exposure limits.
- Ventilation equipment must be explosion proof.
- Exhaust directly to the outside, taking necessary precautions for environmental protection.
- Supply sufficient replacement air to make up for air removed by exhaust systems.

**PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Recommended: neoprene and nitrile  
 Not recommended for heavy use: rubber, PVC, latex

Respirator: NIOSH Approved and equipped with organic-vapor filter

Eye: Safety glasses with side shields, safety goggles or face shields

Clothing: Flame-retardant e.g. Nomex, Proban

**Exposure Limits**

Authority	15 MINS STEL	8-HOURS
OSHA PEL	-	500 ppm (2333 mg/m <sup>3</sup> ) (TWA) (for petroleum distillates)
ACGIH TLV	-	300 ppm (1400mg/m <sup>3</sup> ) (octane,all isomers)



CANADA	-	300 ppm (1400mg/m <sup>3</sup> ) (octane,all isomers)
Alberta, B.C.	-	300 ppm (1400mg/m <sup>3</sup> ) (octane,all isomers)
Ontario	375 ppm (1750 mg/ m <sup>3</sup> )	300 ppm (1400mg/m <sup>3</sup> ) (octane,all isomers)

## 9. Physical and Chemical Properties

<b>Chemical Name:</b> 2,2,4-Trimethylpentane	<b>Molecular Weight:</b> 114.23	<b>Chemical Formula:</b> C <sub>8</sub> H <sub>18</sub> (CH <sub>3</sub> ) <sub>3</sub> CCH <sub>2</sub> CH(CH <sub>3</sub> ) <sub>2</sub>
<b>Chemical Family:</b> Hydrocarbon, Aliphatic	<b>pH:</b> N/AP	
<b>Appearance:</b> Clear, Colorless, Mobile Liquid	<b>Odor:</b> Mild gasoline odor	<b>Odor Threshold:</b> Not Established
<b>Specific Gravity:</b> 0.69194 @20°C (68°F)	<b>Freezing Point:</b> -107°C (-161°F)	<b>Boiling Point:</b> 99°C (211°F)
<b>Percent Volatile:</b> 100 by Volume	<b>Vapor Pressure:</b> 41 mmHg @ 21°C 5.1 kPa @ 20°C 52 mbar @20°C	<b>Vapor Density:</b> 3.9 (air = 1)
<b>Evaporation Rate:</b> <1 (ether = 1) >1 (Butyl Acetate = 1)	<b>Coeff Water/Oil:</b> N/AV	<b>Percent Soluble (@25°C):</b> 0.0002% in water
<b>Others:</b> <ul style="list-style-type: none"><li>• Soluble in acetone, chloroform, dimethylformamide, benzene, toluene, xylene, oils (except castor), carbontetrachloride, alcohol and ether.</li><li>• viscosity: 0.51 mPas @ 22°C (less than 32 saybolt universal seconds)</li><li>• Vapor Pressure: 0.8 psia @ 70°F, 1.7 psia @ 100°F (Reid VP), 13.5 kPa @37.8°C (ASTM D5191), 3.3 psia @ 130°F</li><li>• Henry's Law Constant @ 25°C = 3.04 atm m<sup>3</sup>/mol</li><li>• Enthalpy = 147.2 J/g (360K, 20 bar), 152.3 J/g (360K, 100 bar)</li><li>• Isobaric Heat Capacity = 2.408 J/g K (360K, 20 bar), 2.399 J/g K (360K, 100 bar)</li></ul>		

## 10. Stability and Reactivity

<b>Chemical Stability:</b> Stable under normal temperatures and pressures.
<b>Incompatibility with other Substances:</b> Yes /Oxidizers present a fire and explosion hazard.
<b>Other Reactivity Concerns:</b> Avoid incompatible materials, ignition sources, excess heat, and electrical sparks.
<b>Hazardous Polymerization:</b> Has not been reported to occur under normal temperature and pressure conditions.
<b>Hazardous Decomposition Products:</b> Carbon monoxide, carbon dioxide, irritating and toxic fumes and gases.

**11. Toxicological Information**

<b>Routes of Entry:</b>				
Skin Contact: Yes	Skin Absorption: Yes	Eye Contact: Yes	Inhalation: Yes	Ingestion: Yes
<b>Acute Exposure:</b> See Section 3 (Hazard Identification). Other: Oral administration of 2 mL/kg/day isooctane to rats for 2 days resulted in functional and histological evidence of hepatotoxicity.				
<b>Medical Conditions Aggravated by Exposure:</b> Dermatitis impaired pulmonary function, diseases of the eyes, liver, kidneys or lungs.				
<b>Chronic Exposure:</b> <b>Skin:</b> Repeated and prolonged contact may cause dermatitis due to the defatting action.				
<b>Ingestion and Inhalation:</b> Animal studies indicated that isooctane can induce kidney tumor in male rats; the effects are not considered to be relevant to human since it is a male-rate-specific nephropathy involving the alpha-2μ-globulin protein.				
<b>Carcinogen by NTP:</b> Not Classified	<b>Carcinogen by IARC:</b> Not Classified	<b>OSHA Controlled:</b> Not Classified		
<b>Irritancy:</b> Irritant to eyes, nose, throat, gastrointestinal tract and skin.				
<b>Sensitization:</b> N/AV				
<b>Carcinogenicity:</b> Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.				
<b>Teratogenicity:</b> N/AV				
<b>Reproductive Toxicology:</b> N/AV				
<b>Mutagenicity:</b> N/AV				
<b>Synergistic Products:</b> N/AV				
<b>Target Organs:</b> Central Nervous System (CNS), Kidneys				
<b>Lethality Tests:</b>				
Test:	Value:	Related Information:		
LC50	33.52 mg/l/4 hour	Inhalation – rat (Phillips Petroleum Company)		
LD50	>2000 mg/kg	Skin – rabbit (Phillips Petroleum Company)		
LD50	>5000 mg/kg	Oral – rat (Phillips Petroleum Company)		

## 12. Ecological Information

### Ecological Information:

**Terrestrial Fate:** Photolysis and hydrolysis of isooctane are not expected to be important in soil. Although isooctane may undergo slow biodegradation in soil, volatilization from dry and wet soil surfaces is expected to be more important in the fate process. Isooctane is not expected to leach into groundwater.

**Aquatic Fate:** The hydrolysis of isooctane in water is not expected to be important because the compound does not contain any hydrolyzable group. The photolysis of the compound in water is also expected to be unimportant because isooctane is transparent to wavelengths available in sunlight. Although slow biodegradation may occur in aquatic medium, volatilization from water is expected to be the dominant process. Isooctane is expected to have a half-life of less than 1 day in water. This material may bio-accumulate to some extent.

**Atmospheric Fate:** The reaction of isooctane with atmospheric oxygen may not be important in the atmosphere. The gas-phase reactions of alkanes with ozone and nitrate radicals are of negligible importance as atmospheric loss processes. The half-life of isooctane due to the reaction with atmospheric OH radicals is 4.4 days.

## 13. Disposal Considerations

### Waste Disposal:

Contaminated products such as absorbents, soil, water, etc. should be disposed of according to governmental regulations and guidelines.

Waste should be incinerated, fuels blending, or recycled.

ALWAYS CONTACT A PERMITTED WASTE DISPOSER TO ASSURE COMPLIANCE WITH ALL CURRENT LOCAL, PROVINCIAL, STATE AND FEDERAL LAWS.

## 14. Transport Information

### Special Shipping Information:

- DOT Transportation
  - Shipping Name: Octanes
  - Hazard Class: 3 (Flammable liquid)
  - ID Number: UN 1262
  - Packing Group: II
  - Marking: Octanes, UN 1262
  - Label: Flammable Liquid
  - Placard: Flammable/1262
  - Hazardous Substance/RQ: Not applicable
  - Shipping Description: Octanes, 3 (Flammable liquid, UN 1262, PG II)
  - Packaging References: 49 CFR 173.150, 173.202, 173.242
- TDG
  - Shipping Name: Octanes
  - Hazard Class: 3



**KEYERA**

## Isooctane MSDS

- UN Number: UN1262
- Other Information: Flashpoint -12°C
- IMO (International Marine Organization) and IBC Code (International Bulk Chemical)
  - Pollution Category: X
  - Hazards: P
  - Ship Type 2
  - Tank Type: 2G

### 15. Regulatory Information

#### **Canada:**

Isooctane is listed on Canada's DSL/NDSL List.

WHMIS classification B2, D2B

NFPA Diamond: Fire 3, Toxicity: 1, Reactivity: 0



Isooctane is not listed on Canada's Ingredient Disclosure List.

#### **US/International:**

##### **Atmospheric Standards:**

Listed as a hazardous air pollutant (HAP) generally known or suspected to cause serious health problems. The Clean Air Act, as amended in 1990, directs EPA to set standards requiring major sources to sharply reduce routine emissions of toxic pollutants. EPA is required to establish and phase in specific performance based standards for all air emission sources that emit one or more of the listed pollutants. Isooctane is on the NESHAP Specific Chemicals list and on the Hazardous Air Pollutants list.

##### **TSCA Requirements:**

Pursuant to section 8(d) of TSCA, EPA promulgated a model Health and Safety Data Reporting Rule. The section 8(d) model rule requires manufacturers, importers, and processors of listed chemical substances and mixtures to submit to EPA copies and lists of unpublished health and safety studies. Pentane, 2,2,4-trimethyl- is on this list.

Isooctane is also on the U.S. Federal list for Hazardous Substances (Superfund)

##### **California State Regulatory Program Lists:**

- California Air Toxics "Hot Spots" Chemicals (Assembly Bill 2588)
- California Toxic Air Pollutants (Assembly Bill 1807)



**16. Other Information**

Prepared for: Keyera Health and Safety  
Issue Date: March 5, 2013  
Technical Preparation by: Keyera Alberta Envirofuels (HSE Team)

**Revisions:**

- Original Preparation: February 15, 2001
- 1<sup>st</sup> Revision: November 20, 2002
- 2<sup>nd</sup> Revision: February 26, 2003
- 3<sup>rd</sup> Revision: January 31, 2006
- 4<sup>th</sup> Revision: February 22, 2007
- 5<sup>th</sup> Revision: January 4, 2010
- 6<sup>th</sup> Revision: July 1, 2012
- 7<sup>th</sup> Revision: March 5, 2013

**Disclaimer of Expressed and Implied Warranties**

The information presented in the Material Safety Data Sheet is based on data believed to be accurate as of the date this Material Safety Data Sheet was prepared. However, neither Keyera, nor any of their subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.